

-----  
M A T E R I A L   S A F E T Y   D A T A   S H E E T

-----  
SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

THIS MATERIAL SAFETY DATA SHEET IS AVAILABLE IN SPANISH UPON REQUEST.

LOS DATOS DE SEGURIDAD DEL PRODUCTO PUEDEN OBTENERSE EN ESPANOL SI LO REQUIERE.

PRODUCT NAME : Latex Concrete Sealant  
 UPC NUMBER : 7079818021, 7079818023, 7079818096  
 PRODUCT USE/CLASS : Latex Caulk

MANUFACTURER: DAP INC.  
 2400 BOSTON STREET  
 BALTIMORE, MD 21224

24 HOUR EMERGENCY:  
 TRANSPORTATION: 1-800-535-5053 (352-323-3500)  
 MEDICAL : 1-800-327-3874 (513-558-5111)

PREPARE DATE : 09/03/1997      GENERAL INFORMATION:  
 REVISION NO. : 8                      DAP INC. : 1-888-DAP-TIPS (1-888-327-8477)  
 REVISION DATE: 12/23/1999

-----  
SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % RANGE
01	Ethylene glycol	107-21-1	1.0-5.0 %
02	Calcium Carbonate	1317-65-3	40.0-50.0 %
03	Phthalate Esters	Proprietary	1.0-5.0 %

ITEM	EXPOSURE LIMITS					
	ACGIH		OSHA		COMPANY	
TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN	
01	N.E.	50 ppm*	N.E.	50 ppm	N.E.	NO
02	10 mg/m3	N.E.	10 mg/m3	N.E.	N.E.	NO
03	N.E.	N.E.	N.E.	N.E.	N.E.	no

(See Section 16 for abbreviation legend), \* - TLV-Ceiling Value

Remaining ingredients are not considered hazardous per the OSHA Hazardous Communication Standard.

Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); limits may vary between states.

-----  
SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: CAUTION! May cause eye or skin irritation.

POTENTIAL HEALTH EFFECTS:

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact with skin may cause irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: Vapor may cause nose and throat irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Ingestion of ethylene glycol in excess may lead to respiratory cardiac failure as well as kidney and liver damage.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Ingestion of Ethylene Glycol in excess may lead to respiratory and cardiac failure, and kidney and liver damage.

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY CONTACT: None known.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT EYE CONTACT

-----  
SECTION 4 - FIRST AID MEASURES

EYE CONTACT: Flush with large quantities of water until irritation subsides.

SKIN CONTACT: Wash with soap and water.

INHALATION: Remove to fresh air..

INGESTION: DO NOT INDUCE VOMITING.

COMMENTS: Call Medical in Section 1 if irritation or complications arise from any of the above routes of entry.

-----  
SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: >200 F  
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: N.A.  
UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: N.E.

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM

(Continued on Page 3)  
-----

SECTION 5 - FIRE FIGHTING MEASURES

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Use absorbent material or scrape up dried material and place into containers.

SECTION 7 - HANDLING AND STORAGE

HANDLING INFORMATION: KEEP OUT OF REACH OF CHILDREN. Avoid prolonged or repeated contact with skin. Avoid contact with eyes.

STORAGE INFORMATION: Store away from caustics and oxidizers. Keep containers tightly closed when not in use. Keep containers from excessive heat and freezing. Do not store at temperatures above 120 degrees F.

OTHER PRECAUTIONS: None.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Normal room ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Not required under normal usage and adequate ventilation.

EYE PROTECTION: Safety glasses with side shields recommended.

SKIN PROTECTION: None required.

OTHER PROTECTIVE EQUIPMENT: None.

HYGIENIC PRACTICES: Although this product is not considered an eye irritant, inhalation hazard, or a skin contact hazard under normal conditions, it is advisable that personnel minimize skin contact, inhalation of vapors, and eye contact. Wash contaminated clothing before reuse.

(Continued on Page 4)

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : 210 - 220 F      VAPOR DENSITY : Is heavier than air  
ODOR : Sl. ammonia  
APPEARANCE : Colored paste      EVAPORATION RATE: Is slower than Butyl  
SOLUBILITY IN H2O : Dispersible      Acetate  
SPECIFIC GRAVITY : 1.5196  
VAPOR PRESSURE : 17.5 mm Hg @ 68 F.  
PHYSICAL STATE : Paste

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Strong oxidizers and caustics.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e. CO<sub>x</sub>, NO<sub>x</sub>

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

The toxicological properties of this material are unknown.

SECTION 12 - ECOLOGICAL INFORMATION

No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE MANAGEMENT/DISPOSAL: Dispose of according to Federal, State, and Local Standards. This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulations, 40 CFR Section 261. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

EPA WASTE CODE - If discarded (40 CFR 261): None.

(Continued on Page 5)

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Not Regulated by D.O.T.

DOT HAZARD CLASS: NONE

DOT UN/NA NUMBER: NONE                      PACKING GROUP: NONE

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	WT/WT % RANGE
Ethylene glycol	107-21-1	1.0-5.0 %

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

CHEMICAL NAME	CAS NUMBER
None.	

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

CHEMICAL NAME	CAS NUMBER
Acrylic polymer	TSRN-618608-5059P
Water	7732-18-5
Magnesium Carbonate	546-93-0

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

CHEMICAL NAME	CAS NUMBER
Acrylic polymer	proprietary
Water	7732-18-5
Magnesium Carbonate	546-93-0

(Continued on Page 6)

SECTION 15 - REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer:

CHEMICAL NAME	CAS NUMBER
Chlorothalonil	1897-45-6

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: Not Regulated.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 1      FLAMMABILITY: 1      REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 09/03/1997

REASON FOR REVISION:

SECTION 1: Address change and new emergency contact phone numbers.

VOC less water, less exempt solvent: 50-55 g/L (4.0-5.0 weight %)  
VOC material : 30-35 g/L (3.0-4.0 weight %)

LEGEND: ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS  
N.A. - NOT APPLICABLE  
N.E. - NOT ESTABLISHED  
PEL - PERMISSIBLE EXPOSURE LIMIT  
NTP - NATIONAL TOXICOLOGY PROGRAM  
SARA - SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986  
STEL - SHORT TERM EXPOSURE LIMIT  
TLV - THRESHOLD LIMIT VALUE (8 HR. TIME WEIGHTED AVERAGE OR TWA)  
VOC - VOLATILE ORGANIC COMPOUND  
NJRTK - NEW JERSEY RIGHT TO KNOW LAW  
N.D. - NOT DETERMINED

MSDS# 10010

This data is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

< End OF MSDS >