

REPORT NUMBER: 703 UNIVAR USA INC. PAGE: 001
MSDS NO: OZ32415 MATERIAL SAFETY DATA SHEET
MAINFRAME UPLOAD DATE: 08/18/06 VERSION: 015

PRODUCT: CAUSTIC SODA LIQUID (ALL GRADES)

ORDER NO: 102521
PROD NO : 687077

QUALITY DISCOUNT
METRO RENTON PLANT
1200 MONSTER ROAD

RENTON , WA 98055

UNIVAR USA INC. (425) 889-3400
17425 NE UNION HILL RD , REDMOND , WA 98052

----- EMERGENCY ASSISTANCE -----

FOR EMERGENCY ASSISTANCE INVOLVING CHEMICALS CALL - CHEMTREC
(800)424-9300

PRODUCT NAME: CAUSTIC SODA LIQUID (ALL GRADES)

MSDS NUMBER: OZ32415

DATE ISSUED: 03/10/2006

SUPERSEDES: 12/09/2005

ISSUED BY: 008730

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Distributed by:
Univar USA Inc.
17425 NE Union Hill Road
Redmond, WA 98052
425-889-3400

SUBSTANCE: CAUSTIC SODA LIQUID (ALL GRADES)

TRADE NAMES:

PRODUCT: CAUSTIC SODA LIQUID (ALL GRADES)

ORDER NO: 102521
PROD NO : 687077

Caustic Soda Diaphragm Grade 10%, 15%, 18%, 20%, 25%, 30%, 35%, 40%, 50%, 50%;
Caustic Soda Rayon Grade 18%, 20%, 25%, 30%, 50%; 50% Caustic Soda Rayon
Grade OS; Caustic Soda Membrane 6%, 18%, 20%, 25%, 30%, 48%, 50%; 50% Caustic
Soda Membrane OS; 50% Caustic Soda Diaphragm OS; Caustic Soda Low Salt 50%;
25% Caustic Soda Purified; 50% Caustic Soda Purified; 50% Caustic Soda
Purified OS; Caustic Soda Liquid 70/30; Membrane Blended; 50% Caustic Soda
Membrane (Northeast); 50% Caustic Soda Diaphragm (West Coast); 50% Blended
Rayon Grade Blended; Membrane Cell Liquor

SYNONYMS:
Sodium hydroxide solution; Liquid caustic; Lye solution; Caustic; Lye; Soda
Lye

PRODUCT USE: metal finishing, cleaner, process chemical, petroleum industry

2. HAZARDS IDENTIFICATION

NFPA RATINGS (SCALE 0-4): HEALTH-3 FIRE-0 REACTIVITY-1
HMIS RATINGS (SCALE 0-4): HEALTH=3 FLAMMABILITY-0 REACTIVITY-1

EMERGENCY OVERVIEW:

COLOR: colorless to slightly colored
PHYSICAL FORM: liquid
ODOR: odorless
SIGNAL WORD: DANGER

MAJOR HEALTH HAZARDS: CORROSIVE. CAUSES BURNS TO THE RESPIRATORY TRACT, SKIN,
EYES AND GASTROINTESTINAL TRACT. CAUSES PERMANENT EYE DAMAGE. PHYSICAL
HAZARDS: Mixing with water, acid or incompatible materials may cause
splattering and release of heat.

ECOLOGICAL HAZARDS: This material has exhibited moderate toxicity to aquatic
organisms.

PRECAUTIONARY STATEMENTS: Do not get in eyes, on skin, or on
clothing. Do not breathe vapor or mist. Keep container tightly closed. Wash
thoroughly after handling. Use only with adequate ventilation.

POTENTIAL HEALTH EFFECTS:

INHALATION:
SHORT TERM EXPOSURE: irritation (possibly severe), burns, pulmonary edema
LONG TERM EXPOSURE: to our knowledge, no effects are known

SKIN CONTACT:
SHORT TERM EXPOSURE: irritation (possibly severe), burns
LONG TERM EXPOSURE: dermatitis

REPORT NUMBER: 703 UNIVAR USA INC. PAGE: 003
MSDS NO: OZ32415 MATERIAL SAFETY DATA SHEET
MAINFRAME UPLOAD DATE: 08/18/06 VERSION: 015

PRODUCT: CAUSTIC SODA LIQUID (ALL GRADES)

ORDER NO: 102521
PROD NO : 687077

EYE CONTACT:

SHORT TERM EXPOSURE: irritation (possibly severe), burns, eye damage, blindness
LONG TERM EXPOSURE: visual disturbances

INGESTION:

SHORT TERM EXPOSURE: irritation (possibly severe), burns, nausea, vomiting
LONG TERM EXPOSURE: to our knowledge, no effects are known

CARCINOGEN STATUS:

OSHA: No
NTP: No
IARC: No

3. COMPOSITION INFORMATION ON INGREDIENTS

COMPONENT: WATER

CAS NUMBER: 7732-18-5
PERCENTAGE: 48.5-94.5

COMPONENT: SODIUM HYDROXIDE

CAS NUMBER: 1310-73-2
PERCENTAGE: 5.5-51.5

COMPONENT: SODIUM CHLORIDE

CAS NUMBER: 7647-14-5
PERCENTAGE: 0-5.0

4. FIRST AID MEASURES

INHALATION: If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. If respiration or pulse has stopped, have a trained person administer Basic Life Support (Cardio-Pulmonary Resuscitation/Automatic External Defibrillator) and CALL FOR EMERGENCY SERVICES IMMEDIATELY.

SKIN CONTACT: Immediately flush contaminated areas with water. Remove contaminated clothing, jewelry, and shoes immediately. Wash contaminated areas with soap and water. Thoroughly clean and dry contaminated clothing before reuse. Discard contaminated leather goods. GET MEDICAL ATTENTION IMMEDIATELY.

EYE CONTACT: Immediately flush eyes with a directed stream of water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissues. Washing eyes within several seconds is essential to achieve maximum effectiveness. GET MEDICAL ATTENTION

REPORT NUMBER: 703 UNIVAR USA INC. PAGE: 004
MSDS NO: OZ32415 MATERIAL SAFETY DATA SHEET
MAINFRAME UPLOAD DATE: 08/18/06 VERSION: 015

PRODUCT: CAUSTIC SODA LIQUID (ALL GRADES)

ORDER NO: 102521
PROD NO : 687077

IMMEDIATELY.

INGESTION: Never give anything by mouth to an unconscious or convulsive person. If swallowed, do not induce vomiting. Give large amounts of water. If vomiting occurs spontaneously, keep airway clear. Give more water when vomiting stops. GET MEDICAL ATTENTION IMMEDIATELY.

NOTE TO PHYSICIAN: The absence of visible signs or symptoms of burns does NOT reliably exclude the presence of actual tissue damage. Probable mucosal damage may contraindicate the use of gastric lavage.

5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: Negligible fire hazard.

EXTINGUISHING MEDIA: Use extinguishing agents appropriate for surrounding fire.

FIRE FIGHTING: Move container from fire area if it can be done without risk. Cool containers with water. Wear NIOSH approved positive-pressure self-contained breathing apparatus. Avoid contact with skin.

SENSITIVITY TO MECHANICAL IMPACT: Not sensitive

SENSITIVITY TO STATIC DISCHARGE: Not sensitive

FLASH POINT: not flammable

6. ACCIDENTAL RELEASE MEASURES

OCCUPATIONAL RELEASE:

Wear appropriate personal protective equipment recommended in Section 8 of the MSDS. Completely contain spilled material with dikes, sandbags, etc. Keep out of water supplies and sewers. Reprocess or reuse if possible. Shovel dry material into suitable container. Liquid material may be removed with a vacuum truck. Remaining material may be diluted with water and neutralized with dilute acid. Flush spill area with water, if appropriate. This material is alkaline and may raise the pH of surface waters with low buffering capacity. Releases should be reported, if required, to appropriate agencies. Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800) 424-8802 (USA) or (202)426-2675 (USA).

7. HANDLING AND STORAGE

STORAGE: Store and handle in accordance with all current regulations and

PRODUCT: CAUSTIC SODA LIQUID (ALL GRADES)

ORDER NO: 102521
PROD NO : 687077

standards. Keep container tightly closed and properly labeled. Do not store in aluminum container or use aluminum fittings or transfer lines, as flammable hydrogen gas may be generated. Keep separated from incompatible substances (see Section 10 of the MSDS).

HANDLING: Avoid breathing vapor or mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. When mixing, slowly add to water to minimize heat generation and spattering.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE LIMITS:

SODIUM HYDROXIDE:

2 mg/m3 OSHA TWA

2 mg/m3 OSHA ceiling (vacated by 58 FR 35338, June 30, 1993)

2 mg/m3 ACGIH ceiling

VENTILATION: Provide local exhaust ventilation where dust or mist may be generated. Ensure compliance with applicable exposure limits.

EYE PROTECTION: Wear safety glasses with side shields. Wear chemical safety goggles with a faceshield to protect against skin contact when appropriate. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

CLOTHING: Wear chemical resistant clothing and rubber boots when potential for contact with the material exists. Contaminated clothing should be removed, then discarded or laundered. Always place pants legs over boots.

GLOVES: Wear appropriate chemical resistant gloves.

PROTECTIVE MATERIAL TYPES: butyl rubber, natural rubber, neoprene, nitrile, polyvinyl chloride (PVC), Tychem (R)

IMMEDIATELY DANGEROUS TO LIFE OR HEALTH: 10 mg/m3

RESPIRATOR: Where vapor concentration exceeds or is likely to exceed applicable exposure limits, a NIOSH approved respirator is required. If eye irritation occurs, a full face style mask should be used. When an air-purifying respirator is not adequate or when there are vapor concentrations above 10 ppm or for spills and/or emergencies, a NIOSH approved self-contained breathing apparatus or airline respirator, with full-face piece, is required. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:

liquid

PRODUCT: CAUSTIC SODA LIQUID (ALL GRADES)
ORDER NO: 102521
PROD NO : 687077

APPEARANCE: clear to opaque
COLOR: colorless to slightly colored
ODOR: odorless
BOILING POINT: 230-291 F (110-144 C)
FREEZING POINT: -26 to 59 F (-32 to 15 C)
VAPOR PRESSURE: 13-135 mmHg @ 60 C
VAPOR DENSITY: Not available
SPECIFIC GRAVITY (water=1): 1.11-1.53 @ 15.6 C
DENSITY: 9.27-12.76 lbs/gal @ 15.6 C
WATER SOLUBILITY: 100%
PH: 14.0 (7.5% solution)
VOLATILITY: Not available
ODOR THRESHOLD: Not available
EVAPORATION RATE: Not available
COEFFICIENT OF WATER/OIL DISTRIBUTION: Not available

10. STABILITY AND REACTIVITY

REACTIVITY: Stable at normal temperatures and pressure.

CONDITIONS TO AVOID: Mixing with water, acid or incompatible materials may cause splattering and release of large amounts of heat. Will react with some metals forming flammable hydrogen gas. Carbon monoxide gas may form upon contact with reducing sugars or food and beverage products in enclosed spaces.

INCOMPATIBILITIES: acids, halogenated compounds, prolonged contact with aluminum, brass, bronze, copper, lead, tin, zinc or other alkali sensitive metals or alloys

HAZARDOUS DECOMPOSITION:
Thermal decomposition products: None known.

POLYMERIZATION: Will not polymerize.

11. TOXICOLOGICAL INFORMATION

CAUSTIC SODA LIQUID (ALL GRADES):
TOXICITY DATA: Sodium Hydroxide: 1350 mg/kg Dermal-Rabbit L1350. The severity of the tissue damage is a function of its concentration, the length of tissue contact time, and local tissue conditions. After exposure there may be a time delay before irritation and other effects occur. This material is a strong irritant and is corrosive to the skin, eyes, and mucous membranes. This material may cause severe burns and permanent damage to any tissue with which it comes into contact. Inhalation will cause severe irritation, possible burns with pulmonary edema, which may lead to pneumonitis. Skin contact with this material may cause severe irritation and corrosion of tissue. Eye contact can cause severe irritation, corrosion with possible corneal damage

REPORT NUMBER: 703 UNIVAR USA INC. PAGE: 007
MSDS NO: OZ32415 MATERIAL SAFETY DATA SHEET
MAINFRAME UPLOAD DATE: 08/18/06 VERSION: 015

PRODUCT: CAUSTIC SODA LIQUID (ALL GRADES)

ORDER NO: 102521
PROD NO : 687077

and blindness. Ingestion may cause irritation, corrosion/ulceration, nausea, and vomiting. In general, chronic effects are due to long-term irritation. This material may cause dermatitis on the skin, or recurrent corneal ulceration and visual disturbances. In rare cases reports have noted long-term inhalation causes bronchial inflammatory reaction or obstructive airway dysfunction.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: respiratory system (including asthma and other breathing disorders)

12. ECOLOGICAL INFORMATION

ECOTOXICITY DATA:

FISH TOXICITY: This material has exhibited moderate toxicity to aquatic organisms. For sodium hydroxide: 100 ppm LC50 Daphnia; 25 ppm 24 hours LC50 Brook trout; 48 ppm LC50 King salmon; 33 - 100 ppm 48 hours LC50 Shrimp; 330 - 1000 ppm 48 hours LC50 Cockle

FATE AND TRANSPORT:

BIODEGRADATION: This material is inorganic and not subject to biodegradation.

PERSISTENCE: This material is alkaline and may raise the pH of surface waters with low buffering capacity. This material is believed to exist in the disassociated state in the environment.

BIOCONCENTRATION: This material is believed not to bioaccumulate.

OTHER ECOLOGICAL INFORMATION: This material has exhibited slight toxicity to terrestrial organisms.

13. DISPOSAL CONSIDERATIONS

Reuse or reprocess if possible. Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D002.

14. TRANSPORT INFORMATION

U.S. DOT 49 CFR 172.101:
PROPER SHIPPING NAME: Sodium hydroxide solution
ID NUMBER: UN1824
HAZARD CLASS OR DIVISION: 8 PACKING GROUP: H
LABELING REQUIREMENTS: 8
DOT HAZARDOUS SUBSTANCE(S):
Sodium hydroxide 1000 lb(s) (454 kg(s))

CANADIAN TRANSPORTATION OF DANGEROUS GOODS:
SHIPPING NAME: Sodium hydroxide solution

REPORT NUMBER: 703 UNIVAR USA INC. PAGE: 008
MSDS NO: OZ32415 MATERIAL SAFETY DATA SHEET
MAINFRAME UPLOAD DATE: 08/18/06 VERSION: 015

PRODUCT: CAUSTIC SODA LIQUID (ALL GRADES)

ORDER NO: 102521
PROD NO : 687077

UN NUMBER: UN 1824
CLASS: 8
PACKING GROUP/RISK GROUP: II

15. REGULATORY INFORMATION

U.S. REGULATIONS:
CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4):
SODIUM HYDROXIDE: 1000 LBS RQ

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30):
Not regulated.

SARA TITLE III SARA SECTIONS 311/312 HAZARDOUS CATEGORIES (40 CFR 370.21):

ACUTE: Yes
CHRONIC: No
FIRE: No
REACTIVE: No
SUDDEN RELEASE: No

SARA TITLE III SECTION 313 (40 CFR 372.65): Not regulated.

OSHA PROCESS SAFETY (29CFR1910.119): Not regulated.

FDA: This material has Generally Recognized as Safe (GRAS) status under specific FDA regulations. Additional information is available from the Code of Federal Register (CFR) which is accessible on the FDA's website.

STATE REGULATIONS:

California Proposition 65: This product is not listed, but it may contain contaminants known to the State of California to cause cancer or reproductive toxicity as listed under Proposition 65 State Drinking Water and Toxic Enforcement Act. For additional information, contact Customer Service.

NEW JERSEY WORKER AND COMMUNITY RIGHT TO KNOW:

REPORTING REQUIREMENT:

WATER 7732-18-5 48.5-94.5%
SODIUM HYDROXIDE 1310-73-2 5.5-51.5%
SODIUM CHLORIDE 7647-14-5 0-5.0%

RIGHT TO KNOW HAZARDOUS SUBSTANCE LIST:

SODIUM HYDROXIDE 1310-73-2 5.5-51.5%

SPECIAL HEALTH HAZARD SUBSTANCE LIST:

SODIUM HYDROXIDE 1310-73-2 5.5-51.5%

PENNSYLVANIA RIGHT TO KNOW:

REPORTING REQUIREMENT:

REPORT NUMBER: 703 UNIVAR USA INC. PAGE: 009
MSDS NO: OZ32415 MATERIAL SAFETY DATA SHEET
MAINFRAME UPLOAD DATE: 08/18/06 VERSION: 015

PRODUCT: CAUSTIC SODA LIQUID (ALL GRADES)

ORDER NO: 102521
PROD NO : 687077

WATER 7732-18-5 48.5-94.5%
SODIUM HYDROXIDE 1310-73-2 5.5-51.5%
SODIUM CHLORIDE 7647-14-5 0-5.0%

HAZARDOUS SUBSTANCE LIST:
SODIUM HYDROXIDE 1310-73-2 5.5-51.5%

ENVIRONMENTAL HAZARDOUS SUBSTANCE LIST:
SODIUM HYDROXIDE 1310-73-2 5.5-51.5%

SPECIAL HAZARDOUS SUBSTANCE LIST:
Not regulated.

CANADIAN REGULATIONS:
CONTROLLED PRODUCTS REGULATIONS (CPR):
This product has been classified in accordance with the criteria of the
Controlled Products Regulations (CPR) and the MSDS contains all of the
information required by the CPR.

WHMIS CLASSIFICATION: E.

NATIONAL INVENTORY STATUS:
U.S. INVENTORY (TSCA): All the components of this substance are listed on or
are exempt from the inventory.

TSCA 12(b) EXPORT NOTIFICATION: Not listed.

CANADA INVENTORY (DSL/NDL): All components of this product are listed on the
DSL.

REPORT NUMBER: 703 UNIVAR USA INC. PAGE: 010
MSDS NO: OZ32415 MATERIAL SAFETY DATA SHEET
MAINFRAME UPLOAD DATE: 08/18/06 VERSION: 015

PRODUCT: CAUSTIC SODA LIQUID (ALL GRADES)

ORDER NO: 102521
PROD NO : 687077

----- FOR ADDITIONAL INFORMATION -----

CONTACT: MSDS COORDINATOR UNIVAR USA INC. (425)889-3400
DURING BUSINESS HOURS, PACIFIC TIME

02/28/07 15:34 PRODUCT: 687077 CUST NO: 531480 ORDER NO: 102521

----- NOTICE -----

***** UNIVAR USA INC ("UNIVAR"), EXPRESSLY DISCLAIMS

ALL EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A

PARTICULAR PURPOSE, WITH RESPECT TO THE PRODUCT OR INFORMATION PROVIDED

HEREIN, AND SHALL UNDER NO CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR

CONSEQUENTIAL DAMAGES. **

DO NOT USE INGREDIENT INFORMATION AND/OR PERCENTAGES IN THIS MSDS AS A
PRODUCT SPECIFICATION. FOR PRODUCT SPECIFICATION INFORMATION REFER TO A PRODUCT
SPECIFICATION SHEET AND/OR A CERTIFICATE OF ANALYSIS. THESE CAN BE OBTAINED FROM
YOUR LOCAL UNIVAR SALES OFFICE.

ALL INFORMATION APPEARING HEREIN IS BASED UPON DATA OBTAINED FROM THE
MANUFACTURER AND/OR RECOGNIZED TECHNICAL SOURCES. WHILE THE INFORMATION IS
BELIEVED TO BE ACCURATE, UNIVAR MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR
SUFFICIENCY. CONDITIONS OF USE ARE BEYOND UNIVAR'S CONTROL AND THEREFORE USERS
ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS TO
DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY
ASSUME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM
THE PUBLICATION OR USE OF, OR RELIANCE UPON, INFORMATION CONTAINED HEREIN.
THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT
RELATE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY OTHER
PROCESS.

* * * * * E N D O F M S D S * * * * *